



The wide range of nozzle combinations allows for a variety in diameter of throw and flow rate.

## Application

- Nurseries
- Hot Houses
- As evaporative cooling in poultry sheds

## Features

- Adjustable nozzle trajectory to adjust throw.
- Recommended operating pressure 150 kPa.
- Diameter of throw in excess of 12 metres.
- Wide range of nozzle combinations to deliver the right amount of water.
- 15 mm MBSP Inlet.
- Black polypropylene body

## ORDERING INFORMATION

Code	Description
<b>10142700310</b>	B500 15 mm MBSP with 03/10 nozzles
<b>10142700510</b>	B500 15 mm MBSP with 05/10 nozzles
<b>10142700315</b>	B500 15 mm MBSP with 03/15 nozzles
<b>10142700515</b>	B500 15 mm MBSP with 05/15 nozzles
<b>10142701116</b>	B500 15 mm MBSP with 11/16 nozzles
<b>10142701516</b>	B500 15 mm MBSP with 15/16 nozzles
<b>10142700311</b>	B500 15 mm MBSP with 03/11 nozzles
<b>10142700511</b>	B500 15 mm MBSP with 05/11 nozzles
<b>10142701616</b>	B500 15 mm MBSP with 16/16 nozzles
<b>1014270</b>	B500 15 mm MBSP body only

## Performance Chart

Jet	kPa	Dia (m)	L/h
<b>0310</b>	100	9.2	124
	150	10.6	152
	200	11.1	175
<b>0510</b>	100	9.2	149
	150	10.6	181
	200	11.1	209
<b>0315</b>	100	7.8	166
	150	9.0	205
	200	9.6	237
<b>0515</b>	100	7.8	179
	150	9.0	221
	200	9.6	255
<b>1116</b>	100	10.2	214
	150	11.4	262
	200	11.9	304
<b>1516</b>	100	8.6	235
	150	10.0	289
	200	10.7	333
<b>0311</b>	100	10.8	124
	150	12.0	152
	200	12.4	175
<b>0511</b>	100	10.8	143
	150	12.0	175
	200	12.4	202
<b>1616</b>	100	8.6	247
	150	10.0	304
	200	10.7	351

## Jet Identification

Type	Code	Stamping on jet	Orifice Shape
03	1014261	30	● (with pin)
05	1014262	50	● (with pin)
10	1014264	100	∅
11	1014263	100	●
15	1014266	150	∅
16	1014265	150	●

- 1014398** Polypropylene Sprinkler Base  
 - 15 mm FBSP Outlet  
 - 15 mm MBSP Inlet  
 Mini sprinkler sled for inline tube and mobile applications such as bowling greens. (suitable for tube sizes up to 19 mm)

