



Applications

Suitable for vegetables, ornamentals, landscaped gardens, commercial tree and vine crops.

Rotor Spray™ Mini Sprinklers

Durable and reliable with excellent distribution uniformity. Vari-Rotor Spray™ can be adjusted to reduce volume of flow and radius of throw.

Features

- "C" Frame design for strength and distribution uniformity.
- Full flow spinner suspended between two bearings.
- Inverted model incorporates special dust cover to protect bearing.



Spray™



Inverted Rotor Spray™

ORDERING INFORMATION

Code	Description
10120025	Rotor Spray™ 0.9mm Brown Base
10120015	Rotor Spray™ 1.0mm Blue Base
10120035	Rotor Spray™ 1.3mm Green Base
10120055	Rotor Spray™ 1.5mm Red Base
10120075	Rotor Spray™ 1.8mm Orange Base
10120045	Rotor Spray™ 2.0mm Grey Base
10120205	Vari-Rotor Spray™ Black Base with Shut-off valve
10120125	Inverted Rotor Spray™ 0.9mm Brown Base
10120115	Inverted Rotor Spray™ 1.0mm Blue Base
10120135	Inverted Rotor Spray™ 1.3mm Green Base
10120155	Inverted Rotor Spray™ 1.5mm Red Base



Vari-Rotor Spray™

Performance			Rotor Spray™		Vari-Rotor Spray™		Inverted Rotor Spray™	
			Tested 0.2m above ground		Tested 2.0m above ground		Tested 0.8m above ground	Tested 2.0m above ground
Base Colour and Orifice Size	Pressure (kPa)	Flow (lph)	Diameter of Throw (m)	Stream Height (m)	Diameter of Throw (m)	Stream Height (m)	Diameter of Throw (m)	
Brown 0.9mm	100	31	5.2	0.2			4.0	5.4
	125	35	5.6	0.3			4.2	5.8
	150	38	5.6	0.4			4.2	6.0
Blue 1.0mm	100	38	5.2	0.3			4.2	5.6
	125	42	5.4	0.4			4.4	5.8
	150	46	5.4	0.5			4.6	6.0
Green 1.3mm	100	61	6.0	0.4			4.2	5.8
	150	76	6.9	0.5			4.6	6.2
	200	88	7.2	0.5			5.0	6.6
Red 1.5mm	100	85	6.5	0.4			4.4	6.2
	150	105	7.5	0.4			4.8	6.4
	200	120	8.1	0.4			5.0	7.2
Orange 1.8mm	100	95	6.7	0.3				
	150	117	7.5	0.4				
	200	135	8.4	0.5				
Grey 2.0mm	100	120	6.8	0.4				
	150	150	7.8	0.4				
	200	175	8.0	0.5				
Black 1.5mm	100	0 – 82			0 – 6.5	0 – 0.4		
	150	0 – 105			0 – 7.5	0 – 0.4		
	200	0 – 123			0 – 8.1	0 – 0.4		

Inlet : 10-32 UNF Thread 4mm

Applications

Greenhouses, vegetables and under tree watering.

Excellent single sprinkler distribution. Smooth rotation, robust design, durable construction. The standard sprinkler has a black colour coded 25° trajectory spinner.

Features

- Easily taken apart for servicing.
- Dual outlet sealed spinner enhances performance.
- Nozzle options are coloured to identify flow.



Rotor Max™ Midi Sprinkler

Antelco® Stakes and Fittings

We range a large selection of stakes, fittings, in-line taps and filters.

Please refer to the Toro Ag Price List to see the complete range and codes.

Performance				Rotor Max™ Tested 0.2m Above Ground
Nozzle Colour	Pressure (kPa)	Flow (lph)	Diameter (m)	
Red 2.8mm	100	300	11.0	0.9
	200	400	13.0	1.2
	250	460	13.0	1.2
	300	500	13.0	1.4
Black 3.2mm	100	375	11.0	0.9
	200	540	13.0	1.2
	250	600	13.0	1.2
	300	660	14.0	1.3
Purple 3.8mm	100	550	11.9	0.7
	200	775	13.8	1.0
	250	875	14.0	1.1
	300	975	13.4	1.2

Inlet Thread 1/2" BSPM

Flow Rate

